RMMB

Approvals:

(SP

Project:


DECORATIVE REMOTE

CSA Certified to C22.2 #141.15

MR16 Surface Mount Single, Double or Triple 6V, 12V, & 24V Lamps



DIMENSIONS



The RMMB series of commercial MR16 remotes provides exceptional light output in a compact, traditional design. The die cast, all metal housing is fully adjustable with a friction lock tilt and swivel that can be locked in place with a rear mounted set screw. The canopy is designed to mount directly to typical electrical junction boxes. Available in 6V, 12V and 24V models, all utilizing low glare, MR16 quartz halogen or LED lamps.

MECHANICAL

DESCRIPTION

- Die cast, solid metal housing with die cast, twist lock lamp collar
- Complete adjustablity both tilt and swivel
- 5" diameter canopy standard
- Two canopy mounting holes designed to match standard electrical junction boxes
- White paint finish is standard, black colour is optional
- MR16 lamp designed with low glare reflector and available in 6VDC, 12VDC or 24VDC

ORDERING GUIDE – LED

RMMB	-	_			/	/
Series	Number of heads	Voltage	Wattage	Lamp type	Colour	Options [†]
RMMB	 Single head Double head Triple head Triple head Quad head (require 12" dia. canopy) 	06 - 24 - 6VDC to 24VDC operational	4W - 4 watts	LR - LED	WHT - White (standard) BLK - Black	LCP, VDR, WRG, LXG
			5W - 5 watts	LA - LED		
		12 - 24 - 12VDC to 24VDC operational	6W - 6 watts 7W - 7 watts	LA - LED		

ORDERING GUIDE – INCANDESCENT

RMMB	-	_		/	/
Series	Number of heads	Voltage	Lamp	Colour	Options [†]
RMMB	 Single head Double head Triple head Triple head Quad head (require 12" dia. canopy) 	06V - 6VDC 12V - 12VDC 24V - 24VDC	See lamp selection chart	WHT - White (standard) BLK - Black	LCP, VDR, WRG, LXG

INCANDESCENT LAMP SELECTION

	6 Volts	12 Volts	24 Volts			
MR16 - Small head						
Quartz halogen	08Q, 10Q, 12Q, 20Q	08Q, 10Q, 12Q, 20Q, 35Q, 50Q	10Q, 12Q, 20Q, 35Q, 50Q			

