



# INCANDESCENT EMERGENCY UNIT

## **Illumination**

- Two fully-adjustable 5.4 watt, glare-free lamp heads
- Smooth thermoplastic reflector and plastic lens for optimal light distribution

## **Electrical**

- Dual 120/277 voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- 6V maintenance-free, rechargeable Sealed lead acid battery
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours



## **Mounting**

- Surface mount via easy connect back plate, which fits most standard junction boxes and snaps into place making internal electrical connections
- Top and back K/O available for conduit application
- Suitable for wall or ceiling mount

## **Housing**

- Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish

## **Warranty/Listing**

- Five year warranty on all electronics and housing
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA
- UL listed for wet locations (20°C – 50°C)

## **Dimensions**

