

EBPC-2L

“WAY2GO” plastic compact battery unit
 (Over 4 hours Duration Standalone Unit)
 2 x 2W Crisp White LED Heads

Project: _____
 Type: _____
 Catalogue #: _____
 Drawn by: _____
 Date: _____

The commercial EBPC-2L features a plastic battery unit designed to provide an economical and versatile solution to emergency lighting needs within a small and compact design. The EBPC-2L series is configured with two 2W LED heads and can run for 4 hours duration as a standalone unit.

FEATURES AND SPECIFICATIONS

CIRCUITRY

- 120/347VAC 60Hz Input, field selectable
- Solid state variable rate charger
- Over 4 hours Duration Standalone Unit
- Momentary push button test switch
- Pilot LED for AC ON and CHARGE status
- Fully automatic, current limited charger
- Short circuit protection
- Complete battery recharge in 24 hours
- Maintenance free, sealed lead acid battery

MECHANICAL

- High impact, UV stabilized, thermoplastic construction
- 2 x 2W Crisp White LED Heads
- Low profile, canopy type design with extremely small total footprint
- Universal spider knockout pattern and keyhole mounting slots stamped into back of cabinet
- Unit “quick snaps” onto backplate for simple, speedy installation
- White color is standard

Note: Not intended for flush ceiling mount.


APPROVAL

- CSA Certified to C22.2 #141-15

COMPLIANCE

- Meets requirements of ICES-005

DIMENSIONS



ORDERING GUIDE

EBPC-2L
Series
EBPC-2L

* **QUICK SHIP:** Product availability is subject to change without notice. Please contact your AimLite customer service representative to confirm inventory levels at time of order.



OVERVIEW

Light source	LED
Input voltage	120/347VAC
Emergency duration	Over 4 hours

All products are subject to change or may be discontinued any time without notice.