



**STRIKE FIRST**  
FIRE EXTINGUISHERS



**MULTI-PURPOSE**  
**ABC DRY CHEMICAL**



Meets or exceeds:  
ANSI/UL 299 & 711

English / Spanish labels



Meets or exceeds:  
CAN/ULC-S504 & S508

English / French labels

## Built tough and easy to service

STRIKE FIRST ABC Multi-Purpose Dry Chemical fire extinguishers are designed for:



**CLASS A**  
wood, paper, cloth



**CLASS B**  
flammable liquids & gases



**CLASS C**  
electrical conductivity

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Reinforced, full grip steel handles with polyester powder paint finish
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service


Complies with NFPA 10 Standard

Meets D.O.T. Requirements

U.S.C.G. approved with bracket listed on label

Temperature range: -65°F to 120°F (-54°C to 49°C)

6 Year Warranty



CAPACITY	2.5 lb	5 lb	5 lb	10 lb	20 lb	30 lb
UL Model No.	SF-ABC110ST	SF-ABC210ALV	SF-ABC340ALV	SF-ABC480AP	SF-ABC1020AP	SF-ABC30
ULC Model No.	WBDL-ABC110	WBDL-ABC310LV	WBDL-ABC340LV	WBDL-ABC10	WBDL-ABC20	WBDL-ABC30
UL Rating	1-A : 10-B:C	2-A : 10-B:C	3-A : 40-B:C	4-A : 80-B:C	10-A : 120-B:C	10-A : 120-B:C
ULC Rating	1-A : 10-B:C	3-A : 10-B:C	3-A : 40-B:C	6-A : 80-B:C	10-A : 120-B:C	10-A : 120-B:C
U.S.C.G. Approval	Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size II	Type A Size II, Type B:C Size III	Type A Size II, Type B:C Size IV
Range	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)	10 -15 (3-4.5 m)
Discharge Time	9 sec	13 sec	13 sec	15 sec	28 sec	28 sec
PSI	150	195	195	235	235	195
Height	15 1/4" (39 cm)	15 1/4" (39 cm)	16" (41 cm)	21 1/4" (54 cm)	24" (61 cm)	30 3/4" (78 cm)
Width	3 3/4" (9.5 cm)	6 3/4" (17 cm)	6 3/4" (17 cm)	8" (20.3 cm)	9 1/2" (24 cm)	9 1/2" (24 cm)
Diameter	3 1/8" (8 cm)	4 1/4" (11 cm)	4 1/4" (11 cm)	5 1/8" (13 cm)	7 1/8" (18 cm)	7 1/8" (18 cm)
Weight	4 1/2 lb (2 kg)	10 1/2 lb (4.8 kg)	10 1/2 lb (4.8 kg)	19 1/4 lb (8.8 kg)	35 1/4 lb (16.1 kg)	50 1/3 lb (22.8 kg)
Chrome Option	YES	-	YES	YES	-	-
Standard Bracket	Vehicle / Marine	Wall or Vehicle/ Marine	Wall or Vehicle/ Marine	Wall	Wall	Wall
Optional Brackets	Wall UP2-DB	UB-5DB UB-5MD HDVB-1	UB-5DB UB-5MD HDVB-1	UP-10MD HDVB-2	HDVB-3	HDVB-4 HD-CART



**STRIKE FIRST**  
CORPORATION

777 Tapscott Road  
Scarborough  
Ontario, Canada M1X 1A2

**P** 416 299-7767  
**TF** 1 888 575-1132  
**F** 416 299-8039  
**TF** 1 888 575-1134

**E** info@strike-first.com  
**www.strike-first.com**