

BUILT TOUGH AND EASY TO SERVICE

STRIKE FIRST CARBON DIOXIDE FIRE EXTINGUISHERS ARE DESIGNED FOR:



FLAMMABLE LIQUIDS & GASES

CLASS B



ELECTRICAL CONDUCTIVITY

CLASS C

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin, retaining chain and hose band
- Chrome plated solid brass valve
- Strong impact resistant horn
- Color and bar coded labels for accurate service



LISTED

MEETS OR EXCEEDS:
ANSI/UL 154 & 711



LISTED
HOMOLOGUÉ

MEETS OR EXCEEDS:
CAN/ULC-S503 & S508



STRIKE FIRST
CORPORATION

MANUFACTURING FIRE EQUIPMENT FOR OVER 35 YEARS

CARBON DIOXIDE

- Complies with NFPA 10 Standard
- D.O.T. Approved Cylinder
- U.S.C.G. approved with bracket listed on label
- Temperature range: -22°F to 120°F (-30°C to 49°C)



CAPACITY	5 lbs.	10 lbs.	15 lbs.	20 lbs.
Model No.	SF-5C02A	SF-10C02A	SF-15C02	SF-20C02
UL/ULC Rating	5-B : C	10-B : C	10-B : C	10-B : C
U.S.C.G. Approval	Type B:C Size I	Type B:C Size II	Type B:C Size II	-
Range	6-12 ft (2-2.5 m)	6-12 ft (2-2.5 m)	6-12 ft (2-2.5 m)	6-12 ft (2-2.5 m)
Discharge Time	10 sec	10 sec	15 sec	20 sec
Height	17 1/4" (44 cm)	19 3/4" (50.2 cm)	26 1/4" (66.7 cm)	26 1/4" (66.7 cm)
Width	8 1/2" (21.6 cm)	11 3/4" (30 cm)	11 3/4" (30 cm)	12" (30.5 cm)
Diameter	5 1/4" (13.3 cm)	7" (17.8 cm)	7" (17.8 cm)	8" (21 cm)
Weight	13 1/2 lb (6.12 kg)	28 lb (12.7 kg)	37 lb (12.3 kg)	48 1/8 lb (21.8 kg)
Standard Bracket	Wall	Wall	Wall	Wall
Optional Brackets	HDVB-2	HDVB-3	HDVB-3	-



777 Tapscott Road
Scarborough
Ontario, Canada M1X 1A2

P 416 299-7767
TF 1 888 575-1132
F 416 299-8039
TF 1 888 575-1134

info@strike-first.com | strike-first.com